



Desaérocim P1

Antifoam Agent

Desaérocim P1 is a multi-purpose powdered antifoam. It is particularly recommended for de-airing some mortar and concrete formulas.

CHARACTERISTIC VALUES

- Off-white powder
- Apparent density at 20° C : 0.350 +/- 0.020 kg/dm³ .
- pH at 1% in the water : 6.5-8.5

FIELD OF APPLICATION

Desaérocim P1 is compatible with all cement types.

Desaérocim P1 has received a certificate that allows it to be used in concretes that are in contact with the water dedicated to human consumption.

DOSAGE

The dosage, adapted to each case, has to be defined during prior tests. Nevertheless the use range lies between 0.02 kg and 0.2 kg per 100 kg of cement.

PRECAUTIONS FOR USE

Store **Desaérocim P1** in a location protected against humidity.

SAFETY

- In case of contact with the eyes or skin, rinse with plenty of water.
- Use a dust mask when handling the product.
- It is recommended to wear glasses and gloves when handling the product.
- In all cases, refer to the material safety data sheets.

PACKAGING

Bags of 25 kg.

SERVICE LIFE

- Closed and suitably stored packages may be used for 1 year.

*The material technical and safety data sheets can be consulted on our internet site :
<http://www.axim.fr>*