



Protecim HW

Protection oil for equipment

Protecim HW is an oil with a reinforced physical and chemical action to keep clean mixing plants, mixers, mills and mixing trucks.

CHARACTERISTIC VALUES

- Colour : Light yellow
- Apparent density at 20°C : 0.851 kg/dm³
- Viscosity at 20°C : 20.7 mm² /s
- Viscosity at 40°C : 10.2 mm² /s
- Flash point : 125°C
- Yield point : - 33°C

FIELD OF APPLICATION

Protecim HW is recommended for steel parts and possibly aluminium parts.

Protecim HW should be applied at least once a day on the surface of the material to be protected, even wet, after washing.

DIRECTIONS FOR USE

Protetim HW is an antiblocking agent for equipment in contact with concrete.

Its reinforced chemical action is particularly strong at the level of the concrete-metal interface.

It includes a set of anticorrosion and antioxidant additives.

DOSAGE

Protetim HW is ready to use.

Its covering power lies between 15 to 40 g/m².

PRECAUTIONS FOR USE

Rubber may on the long-term be altered by a repeated contact with this product.

SAFETY

- During spraying, it is recommended to wear eye protection (glasses) and respiratory protection (mask).
- It is recommended to wear gloves when handling the product.
- In all cases, refer to the material safety data sheets.

PACKAGING

- Container of 1000 litres.
- Barrels of 208 litres.
- Kegs of 30 litres.

STORAGE—CONSERVATION

- Expiration date : 2 years as of manufacturing date.

*The material technical and safety data sheets can be consulted on our internet site :
<http://www.axim.fr>*